

## AMENDMENT TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

1. (original) A method of decoding a two-dimensional symbol matrix comprising the steps of:
- acquiring an image of an object;
  - pre-processing said image to obtain a first filtered image and a second filtered image, wherein said first and second filtered images are obtained using different filters; and
  - evaluating each of said first and second filtered images for a valid symbol, wherein said second filtered image is not evaluated unless said first filtered image fails to result in a successful evaluation.
2. (currently amended) The method of claim 1 in which said pre-processing further comprises the steps of:
- performing morphology on said image to obtain said first filtered image and said second filtered image comprises said image without said morphology.
3. (original) The method of claim 1 in which said pre-processing further includes smoothing and sub-sampling of said image.
4. (currently amended) The method of claim 1 in which said step of evaluating each of said first and second filtered image further comprises the steps of:
- defining one of said first and second filtered image as a current image;
  - locating at least one coarse location within said current image that appear to contain a symbol shape to determine a set of symbol candidate locations;
  - refining at least one of said symbol candidate locations to obtain a refined symbol image;
  - evaluating said refined symbol image to determine if it corresponds to a valid symbol; and
  - if said symbol image fails to correspond to a valid symbol, then repeating said steps of locating, ~~discriminating~~, refining and evaluating after having redefined said current image to contain said second filtered image.

09/592,839

Page 3 of 10

5. (original) The method of claim 4 in which said step of locating at least one coarse location further comprises the steps of:
- measuring a first and second derivative of image intensity values across said image; and
  - identifying areas of said image in which said first and second derivatives correspond to areas approximating predetermined shape and size parameters of said two-dimensional symbol;
  - whereby information for each such identified area comprises a location and an orientation.
6. (original) The method of claim 5 in which said step of identifying areas further comprises the steps of:
- filtering the results of said measuring step to remove from further consideration any areas of said image that fail to meet predetermined threshold criteria selected from the set of size, shape, orientation, and location.
7. (original) The method of claim 4 in which said step of refining said at least one of said symbol candidate locations further comprises the steps of:
- performing a variance-based analysis of each of said at least one symbol candidate locations; and
  - reducing said set of symbol candidate locations according to whether a variance calculation for a candidate location exceeds a predetermined threshold.
8. (original) The method of claim 7 in which said variance-based analysis further comprises the steps of:
- dividing each symbol candidate location into a plurality of zones;
  - calculating an intensity variance for each of said zones; and
  - calculating a variance of a sum of the variances for each of said plurality of zones;
  - whereby a single variance value is determined for each candidate location.
9. (original) The method of claim 4 in which said step of evaluating said refined symbol candidate further comprises the steps of:
- performing a generic refinement on said refined symbol to obtain a refined location of a plurality of locator patterns of said symbol candidate;
  - then performing a symbology-specific refinement; and
  - then decoding the result of said symbology-specific refinement.

09/592,839

Page 4 of 10

10. (original) The method of claim 9 in which said generic refinement further comprises the steps of:
- determining a set of two-dimensional areas within said refined symbol candidate, each said two-dimensional area being located and oriented to contain 2D image information corresponding to a locator pattern of a symbol;
  - evaluating said 2D image information to determine a preliminary refined location where said corresponding locator pattern begins and ends; and
  - interpolating said preliminary refined locations obtained from two-dimensional areas corresponding to adjacent locator patterns of said symbol to determine a secondary refined location where each said locator pattern of said symbol begins and ends.
11. (original) The method of claim 9 in which said step of performing a symbology-specific refinement further comprises the step of:
- selecting a model symbol from a predetermined set of model symbols;
  - evaluating said plurality of locator patterns according to said model symbol, to determine which of said locator patterns corresponds to a symbol-specific finder pattern inherent in said model symbol; and
  - refining said symbol candidate by orienting said symbol candidate according to a predefined location of said finder pattern in said selected model symbol.
12. (original) The method of claim 11 in which said step of evaluating further comprises the steps of:
- counting the number of light intensity peaks occurring along an axis of each of said locator patterns;
  - comparing the number of said peaks in each respective locator pattern with a number of peaks expected according to said model pattern; and
  - determining which of said locator patterns corresponds to each locator pattern according to said model pattern.
13. (original) A method of decoding a two-dimensional symbol matrix marked on an object comprising the steps of:
- acquiring an image of an object;
  - pre-processing said image to obtain a morphed image and a non-morphed image;
  - locating a set of at least one coarse location of a symbol image candidate in said morphed image;

09/592,839

Page 5 of 10

filtering said set to discard any coarse location that fails to meet predetermined selection criteria selected from the set of location, orientation and size;

decoding image information within any remaining coarse location according to a symbology-specific decoding method;

evaluating whether said decoding produced a valid result; and

if not, then repeating said steps of filtering, decoding and evaluating using said non-morphed image;

whereby said symbol matrix is either decoded or said object is rejected as not having an observable and decodable symbol.

14. (original) The method of claim 13 in which said step of decoding image information further comprises the steps of:

refining said image information to determine a specific geometry and location of each identifiable locator pattern corresponding to a model symbol image;

processing each identifiable locator pattern to properly orient the remaining image information according to said model symbol image; and

decoding said image information according to said specific geometry, location and orientation.

15. (original) The method of claim 13 in which said step of decoding image information further comprises the step of:

dividing each said coarse location into a plurality of zones;

calculating an intensity variance for each of said zones;

calculating a variance of a sum of the variances for each of said plurality of zones; whereby a single variance value is determined for each coarse location; and

discarding any coarse location having a single variance value less than a predetermined threshold;

defining a refined location of a symbol candidate by processing each remaining coarse location to determine a set of locator patterns within said coarse location;

orienting each refined location according to said set of locator patterns with respect to a selected symbol model defining locator patterns; and

interpreting information in a data region of said symbol candidate according to said orientation, and said locator patterns with respect to said selected symbol model.

09/592,839  
Page 6 of 10

16. (original) An apparatus for decoding a two-dimensional symbol matrix comprising:

an image acquisition device for obtaining an image of an object;  
and

a processor for pre-processing said image to obtain a first filtered image and a second filtered image, wherein said first and second filtered images are obtained using different filters; and

evaluating each of said first and second filtered images for a valid symbol, wherein said second filtered image is not evaluated unless said first filtered image fails to result in a successful evaluation.

17. (original) The apparatus of claim 16 in which said processor further comprises:

a morphology filter for creating said first filtered image;

a coarse location processor for determining a set of coarse locations of symbol candidate information in said image;

a generic filter for removing from said set any coarse locations that fail to meet predetermined criteria selected from the set of size, location, and orientation;

a variance filter for removing from said set any coarse locations having an intensity variance less than a predetermined threshold;

a refinement processor for determining the specific location of image information corresponding to predetermined locator patterns according to a model image selected from a set of model images;

an orientation processor for identification of a symbol orientation according to said information corresponding to predetermined locator patterns;

a symbol decoder for decoding data region information in said image; and

a symbol evaluator to determine if said decoded symbol is a valid symbol.